Euroluce



Aim Small

Flos

No. F0095009

Suspended light fitting. Body in varnished aluminium sheet, shade in photoetched optical polycarbonate. Internal reflector in photo-etched PC. Directionable body. Powered directly from mains. The LED can be dimmed with a «Triac for Led» dimmer approved by Flos.Flos does not respond in case of wrong electrical connection system installations. The cable has a useful length of 9 metres and thus the lamp can be suspended 3 metres from the ceiling. Multiple rose with capacity to connect up to 5 Aim Small also available.

Designed by Ronan & Erwan Bouroullec, 2014



Technical


Photometric

2700K

Phase

90

LED





Mounting	Projectors,Spike	Colour Temp
	Lights,Wall	Dimming
Flux	725lm	CRI
IP Rating	IP20	Source

Physical

Net Weight (kg) 1.35

Electrical

Power	12
Voltage	220-240
Driver	Integrated
Insulation class	П

www.euroluce.com.au | sales@euroluce.com.au | 2024

Our product range updates frequently. All product specifications and data are subject to change without warning in order to improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary, images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all heritad is data. Images and colours are not part of any contract or warron's name wey.