Euroluce



drive

350

driver

350

581

+e=1000000/00000e+

40.5

500

40.5

13.5

Technical		Photometric	
Mounting Flux IP Rating	Track Mounted 1513lm IP20	Colour Temp Dimming Beam Angle CRI Source	3500K (Standard on request) K DALI 35° >90 Track
Physical		Electrical	
Material	Extruded aluminum, thermoplastic material	Power Voltage Driver	13W 13W DALI 220/240 Vac 50/60 Hz

Insulation class

Class II

Incline Dark Performance,

Incline has been designed to bring you a miniaturised yet high performing, integrated track lighting solution. The unique micro fixture is completely

Mid Output - 500mm

integrated inside the 14mm aperture of the 3-circuit track.

Reggiani

No. D.KP63H.WQ21

Black

www.euroluce.com.au | sales@euroluce.com.au | 2024

Our product range updates frequently. All product specifications and data are subject to change without warning in order to improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colour may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.