
Euroluce



In-Finity 100 Recessed No Trim 4000K General Lighting

Flos

No. N10N254G30B

LED modular system for recessed No Trim installation, including LED luminaires, aluminum installation profile and diffusers. Drivers included in lighting modules for 220-240V connection to mains or to other lighting modules.

Designed by Flos Architectural, 2014



Technical

Photometric

I		L		
	25 max	96 100	135	

	Bea	m An
90° 90°	h(m) E(
60° × 60°.	1	282
	2	70
KAHAA	3	3.
	4	1
30° / 2821 cd / 30°	5	1
Luminous flux luminaire 7470 lm		

ngle: 103° E(lx) D(m) 321 2.54 705 5.07 313 7.61 76 10.14 13 12.68

Mounting	Linear Systems	Colo
Flux	7470lm	Dim
IP Rating	IP40	Bear
		CRI

```
Physical
```

```
Length
                   2530
Net Weight (kg)
                   18.80
```

Colour Temp	4000K
Dimming	Non Dimmable
Beam Angle	103
CRI	80

Electrical

65 Power Driver Integrated Insulation class L

www.euroluce.com.au | sales@euroluce.com.au | 2024

Our product range updates frequently. All product specifications and data are subject to cha colours may vary. Images are indicative of the quality and style of the product but may not rep for all technical data. Images and colours are not part of any contract or warranty in any way. effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the mprovements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets ent the precise de